

iSMA-D-PA15C-B1

iSMA-D-PA15C-B1 is 15" Industrial PC Panel with Android 7.1 operating system. It has been designed to simplify the use of Master Application Controller: iSMA-B-MAC36NL.

You can connect it to iSMA-B-MAC36NL, JACE or other supervisor powered by Niagara to display graphics by web page from Niagara system.

As a Panel PC with Android it can be also used as User Interface. You can install a dedicated application that will allow a communication with other devices in BMS system for example our Android application designed for connectivity with Niagara station.

The Aspect Ratio 16:9 with resolution 1920x1080 allows for displaying graphics clearly.

The panel can be built into the wall, it is compatible with VESA.

The panel has an extensive menu in 7 languages, in which we can customize the displayed image.

Key Features

- Android 7.1 operating system
- 15" display with capacitive touch screen
- Aspect Ratio 16:9
- Resolution 1920x1080
- Response time 5 ms
- IP65 for front Panel
- Aluminum alloy enclosure
- VESA compatible
- Available with EU, UK and US power supply.





iSMA-D-PA15C-B1

Specification

Display

- Size 15,6"
- Aspect Ratio 16:9
- Resolution 1920x1080
- Contrast 1000:1
- Luminance 300 nit, up to 1000 nit
- Response time 5 ms
- Active Area (mm) 344.2x193.6
- Display colors 16,7 M (8-bit)
- View angle 89/89/89/89
- 10-point capacitive touch screen

Interfaces

- IP
- TF/SD Card
- 2x RS232
- USB 3.0 and USB 3.0/OTG USB

Interface

• Built-in 7 languages - English, French, German, Spanish, Chinese, Italian, Russian

Power

- Power supply: 110-240 V AC (12V DC), 50/60 Hz
- Power consumption: ≤ 30
- Power standby: ≤ 1.5 W
- Power supply adapters: EU, UK or US

Installation

- Compatible with VESA
- For embedding installation
- Wall mounting

Housing

- Dimension: 420,0x269,0x70,0 mm (16,535x10,591x2,756 in)
- Construction: Aluminum alloy enclosure, color black
- Bezel thickness 3 mm (0,118 in)

Environment

- Operating temperature: -10°C to 60°C (14°F to 140°F)
- Storage temperature: -10°C to 60°C (14°F to 140°F)
- Operation humidity: 10% to 80%
- Storage humidity: 10% to 90%
- Ingress Protection Rating: IP65 for front panel





