

Panasonic ECOi, ECOg and PACi systems to KNX Application

The Panasonic Application has been specially designed to allow bidirectional control and monitoring of Panasonic ECOi, ECOg and PACi systems from a KNX installation.

The solution allows the integration of up to 64 indoor units from a single Interface.

FEATURES

UL Listed.

Direct access to outdoor unit's communication bus.

Scan: Automatic identification of the units presents on the VRF system.

Energy consumption signals from each indoor unit are available.

Outdoor unit's signals available for the integration.

Supports KNX standard datapoints (DPTs) that guarantees a seamless integration with any KNX device or system.

Wide range of monitoring & control datapoints available.

Configuration through IP or USB (Console) port.

Easy integration with Intesis MAPS.


Automatic updates for both Intesis MAPS and interface's firmware.

Use Case

Panasonic VRF systems to KNX Gateway integration example

Panasonic





Description

DIRECT CONNECTION TO VRF OUTDOOR UNITS

The gateway is directly connected to the outdoor unit's communication bus and enables the control of all the indoor units connected to the system.

's allows not only the control and monitoring of the main AC functions but the access to some internal variables of the outdoor units.

FUP BY INTESIS MAPS

The configuration is carried out using the Intesis MAPS software. This one allows you to define your own settings for the device and offers extra

Panasonic

KNX

Intesis

LISTED

1 of 3

functions available for all the new generation gateways. Thanks to the scan function, which allows to automatically discover all the units available in the installation, get the interface ready to work in a really short time.

Intesis MAPS makes it easy to identify any malfunction in the installations thanks to its robust diagnostic feature.

Technical Documentation

User Manual	General information about this product	Download
Installation Manual	Learn how to install the device in your project	Download
Application Wiring Diagram	Review your specific application wiring diagram	Download
HVAC Compatibility tool	Find the appropriate solution for your HVAC integration	Open
EC Declaration of Conformity	Check the product certification	Download
UKCA Certification	Check the product UKCA Certification	Download
Recommendations to avoid polarity issues	How to avoid polarity issues in RS485 Networks	Learn more

Programming Tools

Intesis MAPS	Get access to download the configuration software tool	Download
Intesis MAPS User Manual	General information about Intesis MAPS	Download
eLearning course	Learn the secrets of Intesis MAPS	Enroll now

Commercial Documentation

Marketing Datasheet	Discover all the integration solutions for Panasonic	Download
Intesis Brochure	Know more about the Intesis current available products	Download

File Version Size Read online

ORDER CODES:

IN770AIR00SO000	Intesis multi-brand AC interface with KNX, Serial and IP support - Up to 16 Indoor Units, 32 Outdoor Units
IN770AIR00MO000	Intesis multi-brand AC interface with KNX, Serial and IP support - Up to 64 Indoor Units, 32 Outdoor Units

The order code can differ depending on the product seller and the buyer's location.

- → For the older version, please click here to find the documentation
- → Click here for a larger gateway's capacity

CLUDED COMPONENTS:

Intesis Gateway.

2 of 3

Installation Manual.

USB Configuration cable.

(Power supply not included).

Warranty: 36 months.

Copyright © 2020 HMS Industrial Networks - All rights reserved.



